



FHB Series

SPECIFICATIONS

- Aluminum Housing
- Reflective White Powder Coat Finish
- Highly Efficient Fixture
- T8, T5, or T5HO Lamp Fluorescent Types Available
- LED T8 (BC) Ballast Capitable or (BP) By-Pass
- Minimum 87% Reflectivity
- Available in 4' Length
- Units Equipped with Knockouts and Holes for Pendant Mounting (Conduit by Others)
- Choice of Reflector Material
- Optional Wire Guard
- Optional Wrap Lens
- Optional Emergency Battery
- Optional Daylight Sensor or Motion Sensor

APPLICATIONS

- General Area Lighting
- Warehouse, Industrial, Gymnasium, Commercial Facilities, Convention Centers, Garages
- Retail, Shopping Malls, Recreational Areas

ELECTRICAL

- 120-277V; 50/60Hz
- Optional 480V; 50/60Hz

INSTALLATION

- Surface, Chain or Pendant Mount (Conduit by Others)

CERTIFICATIONS/LISTINGS

- UL Listed

MEMPHIS LIGHTING

PROJECT _____ TYPE _____

QTY _____ NOTES _____ APPROVAL _____

ORDERING/SPECIFYING INFORMATION:

EXAMPLE: FHB 4 F32T8 UNV EA L841

FHB					
Series					
	# of Lamps 4 4 Lamps 6 6 Lamps 8 8 Lamps		Volts UNV 120-277V 480 480V		Options L ___ Lamped WG Wire Guard WL Wrap Lens EM 90 Min Emergency DS Daylight Sensor MS Motion Sensor
		Lamp Type FL LED F28T5 L48BC F32T8 L48BP F54T5HO		Reflector Material EA Enhanced Aluminum SA Specular Aluminum HA High Lustre Aluminum WP White Paint	

SPECIFICATIONS



OPTIONS/ACCESSORIES

Specifications Subject to Change

