


FEATURES

- Anchor Base (AB) or Direct Bury (DB)
- Extruded Aluminum Tube
- Solid Aluminum Base Plate (AB)
- Solid Aluminum Gussets (AB)
- All Parts Circumferentially Welded (AB)
- Black Finish with Optional Colors
- Side or Tenon Mount
- Mounting Heights up to 30 Feet
- Normal Duty .125 Wall
- Medium Duty .188 Wall
- Heavy Duty .250 Wall
- S Strengthening Process Option
- Handhole Access for Wiring
- Pole Base Cover Included
- Optional Bolts (AB)
- Foundation Sold Separately (AB)
- Use CBR-24 Base or Field Cast (AB)

APPLICATIONS

- Parking Areas
- Roadway
- General Area

Concrete Foundation with Embedded L Bolts (Purchase Separately)



PARF Series

Round Aluminum Fluted Pole

Pole Ordering/Specifying Information

SERIES PARF-DB Direct Bury PARF-AB Anchor Base	Size 4 4"	Length ___ Feet	Color BK Black CC Custom Color	Duty ND Normal MD Medium S Strength Process	Mount _ Drill/Cap T 2.38" Tenon T3 3" Tenon	Options AB Bolts

Pole Specification Table

Pole	Overall Height	Mounting Height	Burial Depth	Size	Wall	Bolt Circle	Base Dia/Thick	Bolts
PARF-DB-4-14-ND	14	8	6	4"	0.125	NA	NA	NA
PARF-DB-4-16-ND	16	10	6	4"	0.125	NA	NA	NA
PARF-DB-4-18-ND	18	12	6	4"	0.125	NA	NA	NA
PARF-DB-4-22-ND	22	14	8	4"	0.125	NA	NA	NA
PARF-DB-4-22-MD	22	14	8	4"	0.188	NA	NA	NA
PARF-DB-4-24-MD	24	16	8	4"	0.188	NA	NA	NA
PARF-AB-4-8-ND	8	8	NA	4"	0.125	6-7"	9.5"/.75"	5/8" X 18"
PARF-AB-4-10-ND	10	10	NA	4"	0.125	6-7"	9.5"/.75"	5/8" X 18"
PARF-AB-4-12-ND	12	12	NA	4"	0.125	6-7"	9.5"/.75"	5/8" X 18"
PARF-AB-4-14-ND	14	14	NA	4"	0.125	6-7"	9.5"/.75"	5/8" X 18"
PARF-AB-4-14-MD	14	14	NA	4"	0.188	6-7"	9.5"/.75"	3/4" X 24"
PARF-AB-4-16-MD	16	16	NA	4"	0.188	6-7"	9.5"/.75"	3/4" X 24"

EPA

Pole	120 MPH	140 MPH	150 MPH	160 MPH	170 MPH	180 MPH		
PARF-DB-4-14-ND	10.3	7.2	6.1	5.3	4.6	4.1	-	-
PARF-DB-4-16-ND	7.2	4.8	4.0	3.4	2.9	2.6	-	-
PARF-DB-4-18-ND	5.1	3.3	2.5	2.1	1.8	1.5	-	-
PARF-DB-4-22-ND	3.6	2.0	1.4	1.1	0.8	0.7	-	-
PARF-DB-4-22-MD	5.1	2.9	2.6	2.0	1.6	1.4	-	-
PARF-DB-4-24-MD	4.0	2.3	2.1	1.6	1.3	1.1	-	-
PARF-AB-4-8-ND	10.8	7.6	6.4	5.5	4.8	4.3	-	-
PARF-AB-4-10-ND	7.6	5.1	4.2	3.5	3.1	2.8	-	-
PARF-AB-4-12-ND	5.4	3.4	2.6	2.2	1.9	1.5	-	-
PARF-AB-4-14-ND	3.7	2.1	1.4	1.1	0.9	0.8	-	-
PARF-AB-4-14-MD	5.6	3.1	2.9	2.2	1.8	1.5	-	-
PARF-AB-4-16-MD	4.4	2.5	2.3	1.7	1.4	1.2	-	-

EPA's are Approximate and need to be Confirmed and Certified by a Registered Professional Engineer
 Strengthening Process can be Modified to Produce Higher EPA's
 Consult Factory
Specifications Subject to Change



PROJECT		<h1>SOUTHEAST POLES</h1>		
TYPE	QTY			
NOTES		TITLE Round Aluminum Fluted Pole		
APPROVAL		DRAWING/FILE SE Pole and Bracket Catalog.xlsx		
		DATE 4/26/2018	SCALE N.T.S.	SHEET 2 OF 2