

VPB Series

Ballasted Vapor Proof Pendant Mount



VPB Series

SPECIFICATIONS

- Heavy Die Cast Aluminum Housing
- Gray Powder Coat Finish, Optional Custom Color
- Clear Glass Globe Lens
- Pendant Mount
- HID Porcelain Medium Base 4KV Socket or CF Plug-In Type, GX24Q (Non LED)
- Multiple Light Source Options
- 3K, 4K, 5K or TFL LED Color Options
- Universal Volt LED Driver with Optional Dimming
- Wire Guard Included
- Optional Reflector or Angled Reflector
- Optional Round or Square Swivel Mount (Conduit by Others)

APPLICATIONS

- General Area Lighting
- Industrial Plants, Public Transportation
- Commercial Walkways, Weather Exposed Areas
- Institutional, Vandal Resistant, Loading Docks

ELECTRICAL

- 120-277V: LED 10W & CF 26W, 32W & 42W
- 120V: HPS 35W, 50W, 70W, 100W & 150W
- Quad Volt: HPS & MH 50W & 70W

INSTALLATION

- 3/4" NPS Pendant Mount (Conduit by Others)

CERTIFICATIONS/LISTINGS

- CSA Listed
- Listed for Wet Locations



PROJECT _____ TYPE _____

QTY _____ NOTES _____ APPROVAL _____

ORDERING/SPECIFYING INFORMATION:

EXAMPLE: VPB M 50 Q L



Series

Light Source

- H High Pressure Sodium
- M Metal Halide
- F Compact Fluorescent
- L Light Emitting Diodes

LED Color

- ___ Non LED
- 30K 3000K LED
- 40K 4000K LED
- 50K 5000K LED
- TFL Turtle LED

Options

- L Lamped
- D10 0-10V Dimming (CF/LED)
- R Reflector
- AR Angled Reflector
- RSM Round Swivel Mount
- SSM Square Swivel Mount
- CC Custom Color


Watts

HPS	MH	CF	LED
35	50	26	10
50	70	32	
70		42	
100			
150			

Volts

- 120 120V
- UNV 120-277V
- Q 120/208/240/277V

SPECIFICATIONS



OPTIONS/ACCESSORIES



R Reflector



AR Angled Reflector



RSM Round Swivel Mount



SSM Square Swivel Mount

Specifications Subject to Change

