



CMF LED Series

SPECIFICATIONS

- Die Cast Alloy Aluminum Housing
- Impact Resistant Polycarbonate Lens
- Bronze Powder Coat Finish, Optional Custom Color
- CRI LED Module
- Universal Volt Electronic Driver 120-277V
- 5K LED Color
- Integral Heat Sinking

APPLICATIONS

- General Area Lighting/Sign Lighting
- Industrial Parks, Public Transportation, Airports
- Office Buildings, Medical Facilities, Communities

ELECTRICAL

- 120-277V; 50/60Hz
- 30 Watts; 3,900 Lumens

INSTALLATION

- Mounts with 1/2" Threaded Knuckle

CERTIFICATIONS/LISTINGS

- ETL Listed
- IP65
- Listed for Wet Locations

PROJECT \_\_\_\_\_ TYPE \_\_\_\_\_

QTY \_\_\_\_\_ NOTES \_\_\_\_\_ APPROVAL \_\_\_\_\_

ORDERING/SPECIFYING INFORMATION:

EXAMPLE: CMF L 30 50K UNV



Series

Light Source  
L Light Emitting Diodes


LED Color  
50K 5000K LED

Options  
CC Custom Color

Nominal Watts  
30 30 Watts

Volts  
UNV 120-277V

SPECIFICATIONS



OPTIONS/ACCESSORIES



Specifications Subject to Change

