



CVR LED Series

**SPECIFICATIONS**

- Die Cast Aluminum Housing
- Clear Prismatic Polycarbonate Lens
- Bronze Powder Coat Finish, Optional Custom Color
- CRI LED Aluminum Substrate Board
- Universal Volt LED Driver 120-277V, Optional 480V
- 3K, 4K or 5K LED Color Options
- Stainless Steel Hardware
- Optional Emergency Battery
- Optional Photocell
- Optional Surge Protection
- Optional Dimming

**APPLICATIONS**

- General Area/Garage Lighting
- Platforms, Walkways, Parking, Tunnels
- Schools and Commercial Buildings

**ELECTRICAL**

- 120-277V; 50/60Hz
- Optional 480V; 50/60 Hz
- 54 Watts; 7,436 Lumens

**INSTALLATION**

- Mounts Over Recessed Box or with Surface Conduit

**CERTIFICATIONS/LISTINGS**

- CSA Listed
- IP65
- Listed for Wet Locations




PROJECT \_\_\_\_\_ TYPE \_\_\_\_\_


QTY \_\_\_\_\_ NOTES \_\_\_\_\_ APPROVAL \_\_\_\_\_

ORDERING/SPECIFYING INFORMATION:

EXAMPLE: CVR L 54 40K UNV



**SPECIFICATIONS**



**OPTIONS/ACCESSORIES**

Specifications Subject to Change

